



Data sheet

valid from: 8/15/19



Transition module male thread

* low lead

| | d (mm) | R (inch) | Code | SP | Weight (kg) | h (mm) |
|---|-----------|-------------|--------------------|----|----------------|-----------|
| | 16 - 20 | 3/8 | 760 857 148 | 5 | 0.057 | 42 |
| | 16 - 20 | 1/2 | 762 101 038 | 10 | 0.061 | 42 |
| | 16 - 20 | 3/4 | 762 101 039 | 10 | 0.078 | 43 |
| | 25 - 32 | 3/4 | 762 101 091 | 2 | 0.144 | 51 |
| | 25 - 32 | 1 | 762 101 092 | 2 | 0.189 | 55 |
| * | 16 - 20 | 1/2 | 762 101 265 | 10 | 0.060 | 42 |
| * | 16 - 20 | 3/4 | 762 101 266 | 10 | 0.071 | 43 |
| * | 25 - 32 | 3/4 | 762 101 277 | 2 | 0.135 | 51 |
| * | 25 - 32 | 1 | 762 101 278 | 2 | 0.175 | 55 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>