



## Transition union module flat sealed

Supplied with sealing

\*\* on request

\* low lead

	d (mm)	G (inch)	Part No.	SP	weight (kg)	z (mm)
**	16 - 20	½	<b>762 101 088</b>	2	0.080	41
	16 - 20	¾	<b>762 101 056</b>	2	0.085	35
	25 - 32	¾	<b>762 101 095</b>	2	0.170	48
	25 - 32	1	<b>762 101 096</b>	2	0.233	55
	25 - 32	1 ¼	<b>762 101 097</b>	2	0.266	48
	25 - 32	1 ½	<b>762 101 098</b>	2	0.339	50
*,**	16 - 20	½	<b>762 101 276</b>	2	0.695	41
*	16 - 20	¾	<b>762 101 273</b>	5	0.753	35
*	25 - 32	¾	<b>762 101 281</b>	2	0.155	48
*	25 - 32	1	<b>762 101 282</b>	2	0.180	55
*	25 - 32	1 ¼	<b>762 101 283</b>	2	0.252	48
*	25 - 32	1 ½	<b>762 101 284</b>	2	0.357	50

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>