




Manifold module
with center-to-center distance of 55 mm

* low lead



	d (mm)	Rp (inch)	R outlet (inch)		Part No.	SP	weight (kg)
	16 - 20	3/4	3/4	2-fold	762 101 230	2	0.315
	16 - 20	3/4	3/4	3-fold	762 101 231	2	0.444
	16 - 20	3/4	3/4	4-fold	762 101 232	2	0.573
*	16 - 20	3/4	3/4	2-fold	762 101 294	2	0.315
*	16 - 20	3/4	3/4	3-fold	762 101 295	2	0.444
*	16 - 20	3/4	3/4	4-fold	762 101 296	2	0.573

	d (mm)	Rp (inch)	R outlet (inch)		h (mm)	h1 (mm)	h2 (mm)	L (mm)	L1 (mm)	z (mm)	z1 (mm)
	16 - 20	3/4	3/4	2-fold	123	40	35	33	55	109	19
	16 - 20	3/4	3/4	3-fold	178	40	35	33	55	164	19
	16 - 20	3/4	3/4	4-fold	233	40	35	33	55	219	19
*	16 - 20	3/4	3/4	2-fold	123	40	35	33	55	109	19
*	16 - 20	3/4	3/4	3-fold	178	40	35	33	55	164	19
*	16 - 20	3/4	3/4	4-fold	233	40	35	33	55	219	19

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>